



BM28 CABIN

TECHNICAL SPECIFICATION

LOA	: 28 Ft
Beam	: 9.3 Ft
Dry Weight	: 4200 lbs
Power	: 2x200 Hp
Cruise	: 26-35 Kt
Fast	: 52 Kt
Fuel Capacity	: 2x30 G
Foil	: 316L Stainless Steel

STANDARD SPECIFICATION

BERING MARINE COMPOSITE HULL

Asymmetric foil assist catamaran with 20 deg dead rise at transom
Vacuum infused hull and deck
Vacuum infused cabin
Vacuum infused structural parts

HYPOLON TUBE

7 Chambers Hypalon 1340 gsm Tubes

FUEL SYSTEM

(2)30 Gal Fuel Tanks Located Under Deck w/deck fills, vents, fuel level sensors

ELECTRICAL SYSTEM

(2) Starter Batteries 12/90 AH
(1)12V DC Waterproof Fuse Panel - 10positions
(2) Z4 anodes for cathodic protection
(2)Interior floor lights
(4)LED deck lights
12V USB and lighter port on console
Cable and wiring

ELECTRONICS & NAVIGATIONS

LED navigation lights
Ritchie magnetic compass on helm console
Electric trumpet horn

DECK ACCESSORIES

Helm area; GRP, gelcoated dash console w/ (2) Cupholders
(4)Temperated laminated glass around the cabin
(2)Openable sunroof hatches on the cabin top
(6)Stainless steel hand rails
Stainless steel/Aluminum silver powder coated supported handrails around the console sides
(5)Interior seats in the cabin
Lining for the sides and ceiling of the cabin interior area
(2)Bow area seats unit lids w/gas spring
(2)Cupholders on bow
(2)Stainless steel Bering Marine logo
Stainless steel swimming ladder

SEATING

Bow seating area with backrest
Aft seating area

ANCHORING AND MOORING

Bow locker with hinged hatch
Galvanized anchor with rope and chain combination
(4)Stainless steel mooring cleat
Stainless Steel Bow Eye
(2) Stainless Steel Stern Eyes

BILGE SYSTEM

(3) Rule 500 GPH bilge pumps w/float switches & high water alarm

PAINT & FINISH

Gelcoated finish hull and deck white/light gray color
Gelcoated finish cabin white/light gray color
Gelcoated non-skid surfaces on deck
Prospeed paint and varnish for the stainless steel foil

SAFETY PACKAGE

Type B-1 fire extinguisher